

In the Claims

Please cancel claims 14 and 18 without prejudice. Applicants reserve the right to pursue the cancelled subject matter in a continuing application. Please amend claims 15, 24, 36, and 46 as follows:

1. (Previously Presented) A stool comprising:

a) a base having a front and a back corresponding to a front and back of the stool, respectively, wherein the base is elongated from the back to the front along a longitudinal axis, wherein the base has a convex bottom surface that defines an upwards extending nose at the front of the base;

b) a seat; and

c) a post connecting the base and the seat.

2. (Original) The stool of claim 1 wherein the base further includes a stabilization region, the majority of the stabilization region being located rearward of the post.

3. (Original) The stool of claim 2 wherein the entire stabilization region is located rearward of the post.

4. (Original) The stool of claim 2 wherein the stabilization region is a flattened region.

5. (Original) The stool of claim 1 wherein the base comprises a bottom surface and a top surface, wherein the top surface is concave and comprises at least one storage compartment.

6. (Original) The stool of claim 1 wherein the post is adjustable in height.

7. (Previously Presented) A stool comprising:

a) a base having a front end and a back end corresponding to a front and back of the stool, respectively, wherein the base is elongated from the back to the front along a

longitudinal axis, wherein the base comprises a bottom surface with two opposite sides with convex curvatures, the opposite sides extending between the front end and the back end of the base, the opposite sides converging toward a nose located at the front end of the base;

b) a seat; and

c) a post connecting the base to the seat.

16 ~~8~~⁹. (Original) The stool of claim ~~7~~⁹ wherein the seat has a front and back corresponding to the front and back of the stool, respectively, and first and second sides adjacent the front and back, wherein the seat is elongated from the first and second sides, wherein the seat is elongated transverse with respect to the longitudinal axis of the base, the stool further comprising handles positioned at the first and second sides of the seat.

11 ~~9~~¹⁰. (Original) The stool of claim ~~8~~¹⁰ wherein the seat is contoured.

12 ~~10~~¹¹. (Original) The stool of claim ~~7~~¹¹ wherein the nose is rounded and extends upwardly.

13 ~~11~~¹². (Original) The stool of claim ~~10~~¹² wherein the bottom surface of the base at the nose comprises a non-slip surface.

14 ~~12~~¹³. (Original) The stool of claim ~~11~~¹³ wherein the bottom surface of the base at the nose further comprises discrete protrusions.

15 ~~13~~¹⁴. (Original) The stool of claim ~~12~~¹⁴ further comprising a hole at the back of the base for hanging.

14. (Cancelled)

17 ~~15~~¹⁶. (Currently Amended) A method of gardening, comprising the steps of:
providing a stool having a base with a nose, the base having a convex region and a flattened region, a seat having a contoured region, and a post connecting the seat to the

base, the base being elongated from a back end to a front end along a longitudinal axis,
the flattened region of the base and the contoured region of the seat arranged such that a
user's center of gravity when seated upright is vertically aligned with the flattened region;

placing the stool at a desired garden location and sitting upon the contoured
region of the seat in an upright position, wherein the flattened region stabilizes the user in
the seated upright position;

rolling the stool forward toward the nose of the base to access the desired garden
location wherein the base provides for transitional movement between the flattened
region of the base and the convex region of the base; and

tilting the stool towards a side while still in the forward leaning position to access
other desired garden locations, wherein the convex region of the base provides for
transitional movement from a user's left side to a user's right side;

18. ¹⁷ 1/6. (Original) The method of claim 1/5 wherein the nose includes a non-slip region for
providing added static frictional support between a ground surface and the stool while a
user is in a leaning position.

19. ¹⁷ 1/7. (Original) The method of claim 1/5 further comprising the step of accessing
gardening tools carried in a compartment of the base while seated for gardening purposes.

18. (Cancelled)

20. ¹⁷ 1/8. (Previously Presented) A stool, comprising:

- (a) a seat;
 - (b) a base having a front end and a back end, said base being elongated from
the front end to the back end and defining a longitudinal axis;
 - (c) a post connecting said seat to said base;
 - (d) a stabilization structure positioned rearward of the post;
- said base including a first contour located forward of said post, said first contour
having a first convex curvature in a direction transverse to the longitudinal axis for
allowing side to side pivoting;

said base including a second contour extending a direction along the longitudinal axis for allowing front to back pivoting;

said stabilization region configured to stabilize said stool by limiting side to side pivoting when said stool is upright without interfering with forward pivoting, and without limiting side to side pivoting when said stool is pivoted forward.

- 21 ~~20~~²⁰. (Previously Presented) The stool of claim ~~19~~²⁰, wherein said seat is elongated transversely to the longitudinal axis of said base.
- 22 ~~21~~²⁰. (Previously Presented) The stool of claim ~~19~~²⁰, wherein said seat is shaped such that a seated user's center of gravity is positioned rearward of said post.
- 23 ~~22~~²⁰. (Previously Presented) The stool of claim ~~19~~²⁰, wherein said stabilization structure comprises a flattened region.
- 7 ~~23~~. (Previously Presented) The stool of claim 1 wherein the base tapers from a first width located rearward of the post to a second, narrower width located forward of the post.
- 8 ~~24~~⁷. (Currently Amended) The stool of claim ~~23~~⁷ 24 wherein the base includes a continuous continuously narrowing taper from the first width to the second, narrower width.
- 16 ~~25~~⁹. (Previously Presented) The stool of claim ~~1~~⁹ wherein the seat has a front and back corresponding to the front and back of the stool, respectively, and first and second sides adjacent the front and back, wherein the seat is elongated from the first and second sides, wherein the seat is elongated transverse with respect to the longitudinal axis of the base.
- 24 ~~26~~. (Previously Presented) A stool comprising:
- (a) a base having a width and a length, the length extending from a front end to a back end, the length being greater than the width;

- (b) a seat;
- (c) a post connected to the base and the seat;
- (d) a first contour that extends across the width of the base, the first contour including convex portions on left and right sides of the post; and
- e) a second contour that extends along the length of the base, the second contour including front and rear convex portions located forward and rearward of the post.

- 25 24
- 25 27. (Previously Presented) The stool of claim 26 wherein the seat has a front and back corresponding to the front end and back end of the base, respectively, and first and second sides adjacent the front and back, wherein the seat is elongated from the first and second sides, wherein the seat is elongated transverse with respect to the length of the base.
- 26 28. (Previously Presented) The stool of claim 25 further comprising handles positioned at the first and second sides of the seat
- 27 29. (Previously Presented) The stool of claim 25 wherein the seat is contoured.
- 28 30. (Previously Presented) The stool of claim 24 wherein the front end is rounded and extends upwardly.
- 29 31. (Previously Presented) The stool of claim 28 wherein the base includes a non-slip bottom surface at the front end.
- 30 32. (Previously Presented) The stool of claim 29 wherein the non-slip bottom surface of the base at the front end further comprises discrete protrusions.
- 31 33. (Previously Presented) The stool of claim 29 further comprising a hole at the back end of the base for hanging.

- 32 34. (Previously Presented) The stool of claim ³⁴26 wherein the width includes a primary width located rearward of the post and a secondary, narrower width located forward of the post, the length of the base being greater than both the primary and secondary, narrower widths of the base.
- 33 35. (Previously Presented) The stool of claim ³²34 wherein the base tapers from the primary width to the secondary, narrower width.
- 34 36. (Currently Amended) A method of using a stool, comprising the steps of:
providing a stool having a base with a nose, the base having a convex region and a flattened region, a seat having a contoured region, and a post connecting the seat to the base, the base being elongated from a back end to a front end along a longitudinal axis, the flattened region of the base and the contoured region of the seat arranged such that a user's center of gravity when seated upright is vertically aligned with the flattened region;
placing the stool at a desired location and sitting upon the contoured region of the seat in an upright position, wherein the flattened region stabilizes the user in the seated upright position;
rolling the stool forward toward the nose of the base to access the desired location wherein the base provides for transitional movement between the flattened region of the base and the convex region of the base; and
tilting the stool towards a side while still in the forward leaning position to access other desired locations, wherein the convex region of the base provides for transitional movement from a user's left side to a user's right side;
- 35 37. (Previously Presented) The method of claim ³⁴36 wherein the nose includes a non-slip region for providing added static frictional support between a ground surface and the stool while a user is in a leaning position.
- 34 38. (Previously Presented) The method of claim ³⁴36 further comprising the step of accessing items carried in a compartment of the base while seated.

39. (Previously Presented) A stool comprising:
- 37 a) a base having a front and a back corresponding to a front and back of the stool, respectively, wherein the base is elongated from the back to the front along a longitudinal axis, wherein the base has a convex bottom surface that defines an upwards extending nose at the front of the base;
- b) a seat; and
- c) a support structure connecting the base and the seat.
- 36 40. (Previously Presented) The stool of claim 39 wherein the base further includes a flattened stabilization region.
- 39 41. (Previously Presented) The stool of claim 37 wherein the base comprises a bottom surface and a top surface, wherein the top surface is concave and comprises at least one storage compartment.
- 40 42. (Previously Presented) The stool of claim 37 wherein the support structure is adjustable to position the seat in a raised position or a lowered position relative to the base.
- 41 43. (Previously Presented) The stool of claim 39 wherein the support structure is an adjustable post.
- 42 44. (Previously Presented) A stool comprising:
- a) a base having a front end and a back end corresponding to a front and back of the stool, respectively, wherein the base is elongated from the back to the front along a longitudinal axis, wherein the base comprises a bottom surface with two opposite sides with convex curvatures, the opposite sides extending between the front end and the back end of the base, the opposite sides converging toward a nose located at the front end of the base;
- b) a seat; and
- c) a support structure connecting the base to the seat.

43 45. (Previously Presented) The stool of claim 44 wherein the support structure is an adjustable post.

44 46. (Currently Amended) A method of using a stool, comprising the steps of:
providing a stool having a base with a nose, the base having a convex region and a flattened region, a seat having a contoured region, and a support structure connecting the seat to the base, the base being elongated from a back end to a front end along a longitudinal axis, the flattened region of the base and the contoured region of the seat arranged such that a user's center of gravity when seated upright is vertically aligned with the flattened region;

placing the stool at a desired location and sitting upon the contoured region of the seat in an upright position, wherein the flattened region stabilizes the user in the seated upright position;

rolling the stool forward toward the nose of the base to access the desired location wherein the base provides for transitional movement between the flattened region of the base and the convex region of the base; and

tilting the stool towards a side while still in the forward leaning position to access other desired locations, wherein the convex region of the base provides for transitional movement from a user's left side to a user's right side;

45 47. (Previously Presented) The method of claim 46 wherein the nose includes a non-slip region for providing added static frictional support between a ground surface and the stool while a user is in a leaning position.